

MODEL/PART DESIGNATIONS

BRAND NAME	DESCRIPTION
<i>CUBE Water Treatment System</i>	<i>Waterlogic CUBE</i> – Ambient, Cold, Hot, and Extra Hot
	Model F-FWCU1-M-HCA-TT-SB-IN1
	Serial Number Prefix: 81

SPECIFICATIONS

<u>ITEM</u>	<u>SPECIFICATION</u>
Water	¼" Quick Connect
Cold Water Temperature	Cold Water Temperature – Factory Set Point 5°C (41°F) (Adjustable) 10°C or 15°C (50°F or 60°C)
Cold Water Capacity	1.4 Liter (0.37 Gallons) Cold Tank
Hot Water Temperature	Factory Set Point 86°C (187°F) Programmable 70° - 95°C (158° - 203°F)
Hot Water Capacity	1.3 Liter (0.34 Gallons) Hot Tank
Extra Hot Water Temperature	Extra Hot Water Temperature – Factory Set Point 95°C (203°F)
Hot Tank Manual Reset Overload	105°C (221°F)
Maximum Working Pressure	60 psi (414 kPa) – Use Pressure Regulator
Environmental Temperature	2° - 37°C (35° - 100°F)
Refrigerant Gas	R134a - 55 grams (1.94 oz.) - Hi (280 psi) Low (90 psi)
R134a Pressures	High (230 psi), Low (90 psi)

SHIPPING SPECIFICATIONS

<u>ITEM</u>	<u>SPECIFICATION</u>
Width/Depth/Height #	356 mm (14 inches) x 483 mm (19 inches) x 432mm (17 inches) #
Weight – Dry (w/o packaging)	15 kg (30 pounds)
Shipping Information (length x width x height)	508 mm (20 inches) x 560 mm (22 inches) x 560 mm (22 inches) 8 units per pallet
Shipping Weight – Dry	19 kg. (41 pounds)

ELECTRICAL SPECIFICATIONS

ELECTRICAL SUPPLY	120V/60Hz	15 Amp Service⁺
COMPONENT	POWER (approximate)	AMP DRAW (approximate)
Heater	500 Watts	4.2 Amps
Compressor	210 Watts	1.75 Amps
UV Lamp System	13 Watts	0.11 Amps
CUBE TOTAL	723 Watts	6.06 Amps

#CUBE is 17 inches tall and may not fit between countertops and cabinets - Check installation to ensure adequate clearance.