

### MODEL/PART DESIGNATIONS

BRAND NAME	DESCRIPTION	MODEL - PART NUMBER
<i>infiniti UV</i> Cold and Hot Charcoal and Silver Tower	<i>Waterlogic infiniti UV</i> - Cold and Hot – Charcoal and Silver Tower	IIMHCRC-UV
	F-5001-FS-HC-UT-CS-ION Serial Number Prefix: <b>85</b>	
<i>infiniti UV</i> Cold and Hot Charcoal and Silver Countertop	<i>Waterlogic infiniti UV</i> - Cold and Hot – Charcoal and Silver Countertop	IIHCRC-UV
	F-5001-M-HC-UT-CS-ION Serial Number Prefix: <b>86</b>	

### SPECIFICATIONS

<u>ITEM</u>	<i>infiniti UV Counter Top</i>	<i>infiniti UV Tower</i>
Water Connection	¼" Quick Connect	
Cold Water Temperature	Cold Water Temperature – Factory Set Point 5°C (41°F) Adjustable Parameters 1.1°C to 12.2°C (34°F to 54°F)	
Hot Water Temperature	Factory Set Point 85°C (185°F)	
Hot Water Manual Reset Overload	105°C (221°F)	
Recommended Service Pressure	40-60 psi (275-414 kPa) – Use Pressure Regulator	
Maximum Service Pressure	100 psi (689 kPa) – Use Pressure Regulator	
Rated Service Flow	1.89 Liters per minute (0.5 gallons per minute)	
Environmental Temperature	2°C to 37°C (35°F to 100°F)	
UV Lamp	4W	8W
Heater	500 W	
Refrigerant Gas	R134a, 40g, 1.41 ounces	R134a, 65g, 2.29 ounces
R134a Pressures	High (230 psi), Low (90 psi)	

## SHIPPING SPECIFICATIONS

<b>ITEM</b>	<b><i>infiniti UV Counter Top</i></b>	<b><i>infiniti UV Tower</i></b>
Width/Depth/Height	13.75" x 15.25" x 19"## (35cm x 38.75cm x 48.3cm)	13.5" x 14.5" x 40.5" (34cm x 41cm x 103cm)
Weight (dry)	19.5 kg (42 pounds)	26.5 kg (58 pounds)

## ELECTRICAL SPECIFICATIONS

<b>ELECTRICAL SUPPLY</b>	<b>120V/60Hz, 1PH</b>	<b>15 Amp Service</b>
<b>COMPONENT</b>	<b>POWER (approximate)</b>	<b>AMP DRAW (approximate)</b>
Heater	500	4.2 Amps
Compressor	216	1.8 Amps
UV Lamp System	18	.15 Amps
<b><i>infiniti UV TOTAL</i></b>	<b>734</b>	<b>6.15 Amps</b>

#*infiniti UV Counter Top* is 19 inches. tall and may not fit between countertops and cabinets - Check installation to ensure adequate clearance.