

MODEL/PART DESIGNATIONS

BRAND NAME	DESCRIPTION	MODEL - PART NUMBER
WL100 Counter Top	Waterlogic WL100 Counter Top - Cold and Hot	12-CHCM
	F-100-M-HC-TT-CS-WLU	
	Serial Number Prefix: 59	
WL100 Tower	Waterlogic WL100 Tower - Cold and Hot	12-CHC
	F-100-FS-HC-TT-CS-WLU	
	Serial Number Prefix: 60	

SPECIFICATIONS

<u>ITEM</u>	<u>WL100 Counter Top</u>	<u>WL100 Tower</u>
Water Connection	¼" Quick Connect	
Cold Water Temperature	Cold Water Temperature – Factory Set Point 5°C (41°F) Adjustable to 1.1° - 12.2°C (34° - 54° F)	
Cold Tank Size	2 Liter (.53 Gallons)	
Hot Water Temperature	85°C (185° F)	
Hot Water Manual Reset Overload	105°C (221° F)	
Hot Tank Size	1.6 Liter (.42 Gallons)	
Recommended Service Pressure	40-60 psi (275-414 kPa) – Always Use Pressure Regulator	
Maximum Service Pressure	100 psi (689 kPa) – Use Pressure Regulator	
Rated Service Flow	1.89 Liters per minutes (0.5 gallons per minute)	
Environmental Temperature	2° - 37°C (35° - 100°F)	
Heater	500 W	
Refrigerant Gas	R134a, 40g, 1.41 ounces	R134a, 45g, 1.59 ounces
R134a Pressures	High (230 psi), Low (90 psi)	

SHIPPING SPECIFICATIONS

ITEM	WL100 Counter Top	WL100 Tower
Width/Depth/Height	34cm x 41cm x 45cm (13.5" x 16" x 17.75" #)	34cm x 41cm x 103cm (13.5" x 16" x 40.5")
Weight (dry)	18 kg (40 pounds)	23 kg (50 pounds)

ELECTRICAL SPECIFICATIONS

ELECTRICAL SUPPLY	120V/60Hz, 1PH	15 Amp Service
COMPONENT	POWER (approximate)	AMP DRAW (approximate)
Heater	504	4.2 Amps
Compressor	168	1.4 Amps
WL100 TOTAL	672	5.6 Amps

#WL100 Counter Top is 17.75 in. tall and may not fit between countertops and cabinets - Check installation to ensure adequate clearance.