

## MODEL/PART DESIGNATIONS

BRAND NAME	DESCRIPTION	MODEL PART NUMBER
WL290	<i>Waterlogic WL290</i> – Cold and Hot	GF Max
	F-1010-FS-HC-UT-CS-WLU	
	Serial Number Prefix - 19	

## SPECIFICATIONS

<u>ITEM</u>	
Water Connection	¼" Quick Connect
Cold Water Temperature	Cold Water Temperature – Factory Set Point 5°C (41°F) (Programmable) 3° - 7°C (37° - 45° F.)
Cold Tank and Cold-Water Reservoir Size	4 Liter (1 Gallon) Cold Tank plus 11.2 Liter (3 Gallons) Cold Tank Reservoir Total of 15L (4 Gallons) of Ice Cold water capacity
Hot Water Temperature	Hot Water Temperature – Factory Set Point 85°C (185°F) (Adjustable) 80°C – 93°C (176° - 199°F)
Hot Tank Size	1.6 Liters (0.4 Gallons)
Resettable Hot Tank Overload Devices (High Limit Safety)	105°C (221°F)
Recommended Service Pressure	40-60 psi (275-414 kPa) – Use Pressure Regulator
Maximum Service Pressure	100 psi (689 kPa) – Use Pressure Regulator
Rated Service Flow Out	1.89 Liters per Minute (0.5 gallons per minute)
Environmental Temperature	2° - 37°C (35° - 100°F)
UV Lamp	8 Watts
Heater	500 W
Pump	24V DC – 120 psi – Flow 1000ml/min
Refrigerant Gas	R134a, 58 grams, 2.05 ounces
R134a Pressures	High (230 psi), Low (90 psi)

## SHIPPING SPECIFICATIONS

<u>ITEM</u>	<u>WL290</u>
Width/Depth/Height	380 x 370 x 1,140 cm (150 x 146 x 449 inches)
Weight (dry)	28Kg (62 pounds)
Width/Depth/Height – Box	459 x 419 x 1231 cm (181 x 165 x 485 inches)
Weight (dry) – Boxed	32 Kg (70.5 pounds)

## ELECTRICAL SPECIFICATIONS

<b>ELECTRICAL SUPPLY</b>	<b>120V/60Hz, 1PH</b>	<b>15 Amp Service</b>
<b>COMPONENT</b>	<b>POWER (approximate)</b>	<b>AMP DRAW (approximate)</b>
Heater	500	4.2 Amps
Compressor	207	1.75 Amps
UV Lamp System	8	0.07 Amps
Pump	0.5	0.004 Amps
<b>WL290 TOTAL</b>	<b>716</b>	<b>6.03 Amps</b>