

## MODEL/PART DESIGNATIONS

BRAND NAME	DESCRIPTION	MODEL – PART NUMBER
<b>WL350</b> Counter Top	<b>Waterlogic WL350 Counter Top</b> - Cold and Hot	12-CHCMFW3
	F-2FW-M-HC-TT-CS-INN	
<b>WL350</b> Tower	<b>Waterlogic WL350 Tower</b> - Cold and Hot	12-CHCFW3
	F-2FW-FS-HC-TT-CS-INN	

## SPECIFICATIONS

ITEM	<b>WL350 Counter Top</b>	<b>WL350 Tower</b>
Water Connection	¼" Quick Connect	
Cold Water Temperature	Cold Water Temperature – Factory Set Point 5°C (41°F) Adjustable to 1.1° - 12.2°C (34° - 54° F)	
Cold Tank Size	Countertop - 2 Liters (.5 Gallons) Tower – 4 Liters (1 Gallon)	
Hot Water Temperature	87°C (187°F)	
Hot Tank Size	1.6 Liters (.42 Gallons)	
Hot Water Manual Reset Overload	105°C (221°F)	
Recommended Incoming Feed Pressure	40-60 psi (275-414 kPa) – Use Pressure Regulator	
Maximum Service Pressure	100 psi (689 kPa) – Use Pressure Regulator	
Rated Service Flow Out	1.89 Liters per Minute (0.5 Gallons per Minute) – Firewall Purification	
Environmental Temperature	2° - 37°C (35° - 100°F)	
UV Lamp	15 Watts	15 Watts
Heater	500 W	
Refrigerant Gas	R134a, 40g, 1.41 ounces	R134a, 65g, 2.29 ounces
R134a Pressures	High (230 psi), Low (90 psi)	

## SHIPPING SPECIFICATIONS

<u>ITEM</u>	<u>WL350 Counter Top</u>	<u>WL350 Tower</u>
Width/Depth/Height	34cm x 37cm x 45cm 13.5" x 14.5" x 17.75" #	34cm x 41cm x 104cm 13.5" x 14.5 x 41"
Weight (dry)	26.3 kg (58 pounds)	30 kg (66 pounds)

## ELECTRICAL SPECIFICATIONS

<b>ELECTRICAL SUPPLY</b>	<b>120V/60Hz</b>	<b>15 Amp Service</b>
<b>COMPONENT</b>	<b>POWER (approximate)</b>	<b>AMP DRAW (approximate)</b>
Heater	504	4.2 Amps
Compressor	216	1.8 Amps
UV Lamp System	18	0.15 Amps
<b>WL350 TOTAL</b>	<b>738</b>	<b>6.15 Amps</b>

#WL350 Counter Top is 17.75 in. tall and may not fit between countertops and cabinets - Check installation to ensure adequate clearance.