

## MODEL/PART DESIGNATIONS

BRAND NAME	DESCRIPTION	MODEL – PART NUMBER
<i>WL800</i>	Waterlogic WL800 – Cold and Hot	16-MAXH2

## SPECIFICATIONS

<u>ITEM</u>	<u>WL800</u>
Water Connection	¼" Quick Connect
Cold Water Temperature	Cold Water Temperature – Factory Set Point 5°C (41°F)
Hot Water Temperature	70 - 95°C (158-203°F) Programmable
Recommended Service Pressure	40-60 psi (275-414 kPa) – Use Pressure Regulator
Maximum Working Pressure	60 psi (414 kPa) – Use Pressure Regulator
Environmental Temperature	2 - 37°C (35-100°F)
Refrigerant Gas	R134a – 2.05 oz. (65 grams) - Hi (290 psi) Low (90 psi)
R134a Pressures	High (290 psi), Low (90 psi)
RO Output	284 Liters per day (75 Gallons per Day)

## SHIPPING SPECIFICATIONS

<u>ITEM</u>	<u>DIMENSIONS</u>
Width/Depth/Height	445 mm (17.5 inches) x 508mm (20 inches) x 1257mm (49.5)
Weight – Dry (w/o packaging)	42 kg (93 lb.)
Shipping Information (length x width x height)	546.1 mm (21.5 inches) x 635 mm (25 inches) x 1321 (52 inches) 4 units per pallet
Shipping Weight – Dry	46 kg (103 lb.)

## ELECTRICAL SPECIFICATIONS

<b>15 Amp Service<sup>+</sup></b>
AMP DRAW (approximate) = 6.5 Amps